

Specifications

Roll Width: 54 inches

Roll Size: 40 yards

Weight: 30.75 ± 2 oz per linear yard

Thickness: 42 mils

Cold Crack: -25°F

1000 Hours WeatherOmeter

Abrasion Resistance: No significant wear after 100,000 double rubs with #10 cotton duck using the Wyzenbeek test method

Features & Benefits

- Mildew Resistant
- Formulated without phthalates
- Bromine-free, No Halogenated Flame Retardants (HFRs)
- REACH compliant
- No heavy metals
- No Bisphenol A (BPA)
- No Mercury
- No Ozone Depleting Chemicals
- No PBT's (Persistent Bio accumulative and Toxic Chemicals)

Content

Vinyl

Backing

100% Polyester

Flame Resistance

Manufactured to meet the following flammability* requirements:

Cal TB 117-2013(Sect. 1 - Cover Fabric)

UFAC Class 1

NFPA 260

IMO MSC 88/26/ADD. 2 PART 8 (3.1 and 3.2)

* This term and corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Recommended Applications

Marine

Spa Covers

Hospitality

General Upholstery



Care and Cleaning Instructions

To prevent build up of dirt and contaminants, which may cause permanent staining, periodic cleaning is highly suggested. The frequency of cleaning is dependent upon the environmental conditions the material is subjected to.

For normal cleaning: Most stains can be easily cleaned using warm, soapy water and clear water rinses. Moderate scrubbing with a medium bristle brush will help loosen soiling materials from the depressions of embossed surfaces. For more stubborn stains, use Formula 409® commercially available cleaner in accordance with the manufacturer's instructions. Full strength rubbing alcohol or mineral spirits* may be tried cautiously as a last resort on very stubborn stain, if the above suggestions do not work. Indiscriminate use of any solvent, or solvent containing cleaner, can severely damage or discolor vinyl. Always follow with a clear water rinse after cleaning with solvents.

Note: Detergents should never be used on a regular or repeated basis for normal cleaning. Morbern recommends repeated rinsing with clear water after any cleaning procedure. When opening a new container, please test the cleaner in an inconspicuous area as cleaning manufacturers may change formula without notice. Morbern cannot be responsible when unknown changes are made by the manufacturer of the cleaner to their formulations.

*Caution: Exercise care as these solvents are flammable. Use only small quantities of solvents and keep clear of any sources of ignition. Wear protective gloves and ensure cleaning takes place in a well ventilated area.

Note: Stronger cleaners, detergents, and solvents may be effective in stain removal, but can cause either immediate damage or slow deterioration. Many such materials are wrongly recommended in marine and other related industries. The use of such cleaners is at the owner's own risk.

This information is offered for your general guidance only. It is accurate to the best of our knowledge at the time of printing, but it is not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with the laws and procedures applicable to the safe handling and use of this material.

888-MORBERN
www.morbern.com



Seabrook



Morbern is an ISO
9001:2015 Certified
Producer

©2020 Morbern, Inc.